

United States Patent [19]

Cohn et al.

Patent Number: [11]

6,053,929

Date of Patent: [45]

*Apr. 25, 2000

SURGICAL SCALPEL

Inventors: Simon Cohn, North Arlington; Charles

G. Hwang, Jersey City; Bradley M. Wilkinson, North Heledon, all of N.J.; Ann C. Eckert, Easton, Pa.; Noel Gharibian, Glendale, Calif.

Assignee: Becton Dickinson and Company,

Franklin Lakes, N.J.

[*] Notice: This patent is subject to a terminal dis-

claimer.

Appl. No.: 09/273,677

[22] Filed: Mar. 22, 1999

Related U.S. Application Data

Continuation-in-part of application No. 09/052,588, Mar. 3, 1998, Pat. No. 5,938,676, which is a continuation-in-part of application No. 08/666,734, Jun. 18, 1996, Pat. No. 5,938, 675, which is a continuation-in-part of application No. 08/376,065, Jan. 20, 1995, Pat. No. 5,527,329, which is a continuation of application No. 08/163,938, Dec. 8, 1993, abandoned.

[51]

U.S. Cl. 606/167; 30/2; 30/151; 30/335

Field of Search 606/166, 167, 606/170, 172, 181, 182, 185; 30/2, 151, 162, 164, 167, 286, 335

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,491,132 1/1985 Aikins 606/167 5,207,696 5/1993 Matwijcow 606/167

Primary Examiner—Gary Jackson Assistant Examiner—William Lewis

Attorney, Agent, or Firm—Arthur D. Dawson; Scott S. Servilla

[57] **ABSTRACT**

A surgical scalpel includes an elongate handle defining a longitudinal axis and having a proximal end and a distal end. The scalpel has a cartridge removably mounted to the handle that has a blade holder with a proximal end and a distal end. There is a blade fixedly attached to blade holder disposed so that the blade projects distally outwardly when the cartridge is mounted on the handle. The cartridge also has a shield with a proximal end, a distal end and a bottom mounted onto the blade holder. The shield is slidably movable between a distal position where the shield substantially prevents inadvertent access to the blade and a proximal position where the shield substantially surrounds a portion of the handle and the blade is exposed for use. The cartridge is releasably mountable to the handle and has elements for substantially preventing movement of the shield with respect to the blade holder unless the cartridge is mounted on the handle. The cartridge further including elements for substantially preventing an inadvertent movement of the shield to the proximal position thereby to expose the blade as the cartridge is being mounted to the handle.

29 Claims, 44 Drawing Sheets

